

SIMATIC S7-400, SM 422 DIGITAL OUTPUT MODULE, OPTIC.
ISOLATED, 32 DO, 24V DC, 0.5A



Supply voltage

Load voltage L+

• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V

Input current

from load voltage L+ (without load), max.	30 mA
from backplane bus 5 V DC, max.	200 mA

Power losses

Power loss, max.	4 W
------------------	-----

Digital outputs

Number of digital outputs	32
Limitation of inductive shutdown voltage to	-27 V

Switching capacity of the outputs

• Lamp load, max.	5 W
-------------------	-----

Output voltage

• for signal "1", min.	L+ (-0.3 V)
------------------------	-------------

Output current

• for signal "1" rated value	0.5 A
• for signal "1" permissible range for 0 to 60 °C, min.	5 mA
• for signal "1" permissible range for 0 to 60 °C, max.	0.6 A
• for signal "0" residual current, max.	0.3 mA
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
Aggregate current of outputs (per group)	
all mounting positions	
— up to 60 °C, max.	2 A; 8 adjacent outputs each
Cable length	
• Cable length, shielded, max.	1 000 m
• Cable length unshielded, max.	600 m
Galvanic isolation	
Galvanic isolation digital outputs	
• between the channels, in groups of	32
• between the channels and the backplane bus	Yes
Isolation	
Isolation checked with	500 V DC
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	600 g
last modified:	01.12.2014