

SIMATIC S7-400, SM 431 ANALOG INPUT MODULE OPTIC.
ISOLATED, 8 AI, 14 BIT RESOLUTION, U//RESIST./
THERMOEL/PT100



Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V; Only required for supplying 2-wire transmitters
<ul style="list-style-type: none"> Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	200 mA
from backplane bus 5 V DC, max.	600 mA
Power losses	
Power loss, typ.	3.5 W
Hardware configuration	
Slots	
<ul style="list-style-type: none"> Required slots 	1
Analog inputs	
Number of analog inputs	8
Number of analog inputs for voltage/current measurement	8
Number of analog inputs for resistance measurement	4

permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA; Permanent
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	Yes
• Resistance thermometer	Yes
• Resistance	Yes
Input ranges (rated values), voltages	
• 1 to 5 V	Yes
• Input resistance (1 to 5 V)	1 M Ω
• -1 V to +1 V	Yes
• Input resistance (-1 V to +1 V)	1 M Ω
• -10 V to +10 V	Yes
• Input resistance (-10 V to +10 V)	1 M Ω
• -2.5 V to +2.5 V	Yes
• Input resistance (-2.5 V to +2.5 V)	1 M Ω
• -250 mV to +250 mV	Yes
• Input resistance (-250 mV to +250 mV)	1 M Ω
• -5 V to +5 V	Yes
• Input resistance (-5 V to +5 V)	1 M Ω
• -500 mV to +500 mV	Yes
• Input resistance (-500 mV to +500 mV)	1 M Ω
• -80 mV to +80 mV	Yes
• Input resistance (-80 mV to +80 mV)	1 M Ω
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	50 Ω
• 4 to 20 mA	Yes
• Input resistance (4 to 20 mA)	50 Ω
Input ranges (rated values), thermoelements	
• Type B	Yes
• Type E	Yes
• Type J	Yes
• Type K	Yes
• Type L	Yes
• Type N	Yes
• Type R	Yes
• Type S	Yes
• Type T	Yes
• Type U	Yes
Input ranges (rated values), resistance thermometer	

• Ni 100	Yes
• Input resistance (Ni 100)	1 MΩ
• Ni 1000	Yes
• Input resistance (Ni 1000)	1 MΩ
• Pt 100	Yes
• Input resistance (Pt 100)	1 MΩ
• Pt 1000	Yes
• Pt 10000	Yes
• Pt 200	Yes
• Input resistance (Pt 200)	1 MΩ
• Pt 500	Yes
• Input resistance (Pt 500)	1 MΩ
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes
• Input resistance (0 to 150 ohms)	1 MΩ
• 0 to 300 ohms	Yes
• Input resistance (0 to 300 ohms)	1 MΩ
• 0 to 48 ohms	Yes
• Input resistance (0 to 48 ohms)	1 MΩ
• 0 to 600 ohms	Yes
• Input resistance (0 to 600 ohms)	1 MΩ
• 0 to 6000 ohms	Yes; Usable up to 5000 Ohm
• Input resistance (0 to 6000 ohms)	1 MΩ
Thermocouple (TC)	
Temperature compensation	
— internal temperature compensation	No
— external temperature compensation with compensations socket	Yes
— external temperature compensation with Pt100	Yes
— dynamic reference temperature value	Yes
Characteristic linearization	
• Parameterizable	Yes
— for thermocouples	Type B, E, J, K, L, N, R, S, T, U
— for resistance thermometer	Pt100, Pt200, Pt500, Pt1000, Ni100, Ni1000
Cable length	
• Cable length, shielded, max.	200 m; 50 m with thermocouples and input ranges <= 80 mV
Analog value creation	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit; with activated filtering: 16 bits
• Integration time, parameterizable	Yes
• Basic conversion time, ms	20.1 / 23.5 ms

• Integration time, ms	16,7 / 20 ms
• Basic conversion time, including integration time, ms	
— additional conversion time for wire break monitoring	4,3 ms
— additional conversion time for resistance measurement	40.2 / 47 ms
— additional conversion time for wire break monitoring and resistance measurement	5,5 ms
• Interference voltage suppression for interference frequency f1 in Hz	60 / 50 Hz

Encoder

Connection of signal encoders

• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes
• for resistance measurement with two-wire connection	Yes; Line resistances are also measured
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes

Errors/accuracies

Operational limit in overall temperature range

• Voltage, relative to input area, (+/-)	0.38 %; +/-0.38% at +/-80 mV; +/-0.35% at +/-250 mV, +/-500mV, +/-1 V, +/-2,5 V, +/-5 V, 1 to 5 V, +/-10 V
• Current, relative to input area, (+/-)	0.35 %; +/-20 mA, 0 to 20 mA, 4 to 20 mA
• Resistance, relative to input area, (+/-)	0.5 %
• Resistance thermometer, relative to input area, (+/-)	0.5 %

Basic error limit (operational limit at 25 °C)

• Voltage, relative to input area, (+/-)	0.15 %; +/-0.15% (+/-250 mV, +/-500 mV, +/-1 V, +/-2.5 V, +/-5 V, 1 to 5 V, +/- 10 V); +/-0.17% (+/- 80 mV);
• Current, relative to input area, (+/-)	0.15 %; +/-20 mA, 0 to 20 mA, 4 to 20 mA
• Resistance, relative to input area, (+/-)	0.15 %; +/-0.15% at 0 to 48 ohms (4-conductor measurement), 0 to 150 ohms (4-conductor measurement), 0 to 300 ohms (4-conductor measurement), 0 to 5000 ohms (4-conductor measurement, in range of 6000 ohms); +/-0.3% at 0 to 300 ohms (3-conductor measurement), 0 to 600 ohms (3-conductor measurement), 0 to 5000 ohms (3-conductor measurement, in range of 6000 ohms)
• Resistance thermometer, relative to input area, (+/-)	0.3 %

Galvanic isolation

Galvanic isolation analog inputs

• Galvanic isolation analog inputs	Yes; internal/external
------------------------------------	------------------------

- between the channels

No

Permissible potential difference

between the inputs (UCM)

120 V AC

Isolation

Isolation checked with

2120 V DC between bus and L+/M; 2120 V DC between bus and analog part; 500 V DC between bus and local ground; 707 V DC between analog part and L+/M; 2120 V DC between analog part and local ground; 2120 V DC between L+/M and local ground

Dimensions

Width

25 mm

Height

290 mm

Depth

210 mm

Weights

Weight, approx.

500 g

last modified:

14.10.2014