



SIMATIC S7-1500 Analog input module, AI 8xU/I/R/RTD BA, 16 bit resolution, Accuracy 0.5%, 8 channels in groups of 8; Common mode voltage 4 V DC, Diagnostics; Hardware interrupts; Delivery including infeed element, shield bracket and shield terminal: Front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	AI 8xU/I/R/RTD BA
HW functional status	FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V15.1 / V16
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSI</li> </ul>	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	No
Power	
Power available from the backplane bus	0.85 W
Power loss	
Power loss, typ.	0.9 W
Analog inputs	
Number of analog inputs	8
<ul style="list-style-type: none"> <li>For current measurement</li> </ul>	8
<ul style="list-style-type: none"> <li>For voltage measurement</li> </ul>	8
<ul style="list-style-type: none"> <li>For resistance/resistance thermometer measurement</li> </ul>	8
permissible input voltage for voltage input (destruction limit), max.	12 V; 12 V continuous, 30 V for max. 1 s
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	230 ... 370 $\mu$ A
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>0 to +5 V</li> </ul>	No
<ul style="list-style-type: none"> <li>0 to +10 V</li> </ul>	No
<ul style="list-style-type: none"> <li>1 V to 5 V</li> </ul>	Yes
— Input resistance (1 V to 5 V)	10 M $\Omega$

<ul style="list-style-type: none"> <li>• -1 V to +1 V <ul style="list-style-type: none"> <li>— Input resistance (-1 V to +1 V)</li> </ul> </li> <li>• -10 V to +10 V <ul style="list-style-type: none"> <li>— Input resistance (-10 V to +10 V)</li> </ul> </li> <li>• -2.5 V to +2.5 V</li> <li>• -25 mV to +25 mV</li> <li>• -250 mV to +250 mV</li> <li>• -5 V to +5 V <ul style="list-style-type: none"> <li>— Input resistance (-5 V to +5 V)</li> </ul> </li> <li>• -50 mV to +50 mV <ul style="list-style-type: none"> <li>— Input resistance (-50 mV to +50 mV)</li> </ul> </li> <li>• -500 mV to +500 mV <ul style="list-style-type: none"> <li>— Input resistance (-500 mV to +500 mV)</li> </ul> </li> <li>• -80 mV to +80 mV</li> </ul>	<p>Yes</p> <p>10 M<math>\Omega</math></p> <p>Yes</p> <p>10 M<math>\Omega</math></p> <p>No</p> <p>No</p> <p>No</p> <p>Yes</p> <p>10 M<math>\Omega</math></p> <p>Yes</p> <p>10 M<math>\Omega</math></p> <p>Yes</p> <p>10 M<math>\Omega</math></p> <p>No</p>
<b>Input ranges (rated values), currents</b>	
<ul style="list-style-type: none"> <li>• 0 to 20 mA <ul style="list-style-type: none"> <li>— Input resistance (0 to 20 mA)</li> </ul> </li> <li>• -20 mA to +20 mA <ul style="list-style-type: none"> <li>— Input resistance (-20 mA to +20 mA)</li> </ul> </li> <li>• 4 mA to 20 mA <ul style="list-style-type: none"> <li>— Input resistance (4 mA to 20 mA)</li> </ul> </li> </ul>	<p>Yes</p> <p>25 <math>\Omega</math>; Plus approx. 42 ohms for overvoltage protection by PTC</p> <p>Yes</p> <p>25 <math>\Omega</math>; Plus approx. 42 ohms for overvoltage protection by PTC</p> <p>Yes</p> <p>25 <math>\Omega</math>; Plus approx. 42 ohms for overvoltage protection by PTC</p>
<b>Input ranges (rated values), thermocouples</b>	
<ul style="list-style-type: none"> <li>• Type B</li> <li>• Type C</li> <li>• Type E</li> <li>• Type J</li> <li>• Type K</li> <li>• Type L</li> <li>• Type N</li> <li>• Type R</li> <li>• Type S</li> <li>• Type T</li> <li>• Type U</li> <li>• Type TXK/TXK(L) to GOST</li> </ul>	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
<b>Input ranges (rated values), resistance thermometer</b>	
<ul style="list-style-type: none"> <li>• Cu 10</li> <li>• Cu 10 according to GOST</li> <li>• Cu 50</li> <li>• Cu 50 according to GOST</li> <li>• Cu 100</li> <li>• Cu 100 according to GOST</li> <li>• Ni 10</li> <li>• Ni 10 according to GOST</li> <li>• Ni 100 <ul style="list-style-type: none"> <li>— Input resistance (Ni 100)</li> </ul> </li> <li>• Ni 100 according to GOST</li> <li>• Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (Ni 1000)</li> </ul> </li> <li>• Ni 1000 according to GOST</li> <li>• LG-Ni 1000 <ul style="list-style-type: none"> <li>— Input resistance (LG-Ni 1000)</li> </ul> </li> <li>• Ni 120</li> <li>• Ni 120 according to GOST</li> <li>• Ni 200</li> <li>• Ni 200 according to GOST</li> <li>• Ni 500</li> <li>• Ni 500 according to GOST</li> <li>• Pt 10</li> <li>• Pt 10 according to GOST</li> <li>• Pt 50</li> <li>• Pt 50 according to GOST</li> <li>• Pt 100 <ul style="list-style-type: none"> <li>— Input resistance (Pt 100)</li> </ul> </li> <li>• Pt 100 according to GOST</li> </ul>	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>Yes; Standard/climate</p> <p>10 M<math>\Omega</math></p> <p>No</p> <p>Yes; Standard/climate</p> <p>10 M<math>\Omega</math></p> <p>No</p> <p>Yes; Standard/climate</p> <p>10 M<math>\Omega</math></p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>Yes; Standard/climate</p> <p>10 M<math>\Omega</math></p> <p>No</p>

<ul style="list-style-type: none"> <li>• Pt 1000 — Input resistance (Pt 1000)</li> <li>• Pt 1000 according to GOST</li> <li>• Pt 200</li> <li>• Pt 200 according to GOST</li> <li>• Pt 500</li> <li>• Pt 500 according to GOST</li> </ul>	Yes; Standard/climate 10 MΩ No No No No No
<b>Input ranges (rated values), resistors</b>	
<ul style="list-style-type: none"> <li>• 0 to 150 ohms</li> <li>• 0 to 300 ohms</li> <li>• 0 to 600 ohms — Input resistance (0 to 600 ohms)</li> <li>• 0 to 3000 ohms</li> <li>• 0 to 6000 ohms — Input resistance (0 to 6000 ohms)</li> <li>• PTC — Input resistance (PTC)</li> </ul>	No No Yes 10 MΩ No Yes 10 MΩ Yes 10 MΩ
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	200 m; 50 m at 50 mV
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating
<b>Integration and conversion time/resolution per channel</b>	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> <li>• Integration time, parameterizable</li> <li>• Integration time (ms)</li> <li>• Basic conversion time, including integration time (ms) — additional conversion time for wire-break monitoring — additional conversion time for resistance measurement</li> <li>• Interference voltage suppression for interference frequency f1 in Hz</li> </ul>	16 bit Yes 2,5 / 16,67 / 20 / 100 ms 10 / 24 / 27 / 107 ms 4 ms (to be considered in R/RTD/U 1 to 5 V measurement) 8 ms 400 / 60 / 50 / 10 Hz
<b>Smoothing of measured values</b>	
<ul style="list-style-type: none"> <li>• parameterizable</li> <li>• Step: None</li> <li>• Step: low</li> <li>• Step: Medium</li> <li>• Step: High</li> </ul>	Yes Yes Yes Yes Yes
<b>Encoder</b>	
<b>Connection of signal encoders</b>	
<ul style="list-style-type: none"> <li>• for voltage measurement</li> <li>• for current measurement as 2-wire transducer</li> <li>• for current measurement as 4-wire transducer</li> <li>• for resistance measurement with two-wire connection</li> <li>• for resistance measurement with three-wire connection</li> </ul>	Yes Yes; with external supply Yes Yes; Only for PTC Yes; All measuring ranges except PTC; internal compensation of the cable resistances
<b>Errors/accuracies</b>	
Linearity error (relative to input range), (+/-)	0.1 %
Temperature error (relative to input range), (+/-)	0.006 %/K
Crosstalk between the inputs, max.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.1 %
<b>Operational error limit in overall temperature range</b>	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> <li>• Current, relative to input range, (+/-)</li> <li>• Resistance, relative to input range, (+/-)</li> <li>• Resistance thermometer, relative to input range, (+/-)</li> </ul>	0.5 % 0.5 % 0.5 % Ptxxx Standard: ±1.2 K, Ptxxx Climate: ±0.8 K, Nixxx Standard: ±0.8 K, Nixxx Climate: ±0.8 K
<b>Basic error limit (operational limit at 25 °C)</b>	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> <li>• Current, relative to input range, (+/-)</li> <li>• Resistance, relative to input range, (+/-)</li> <li>• Resistance thermometer, relative to input range, (+/-)</li> </ul>	0.3 % 0.3 % 0.3 % Ptxxx Standard: ±1.0 K, Ptxxx Climate: ±0.5 K, Nixxx Standard: ±0.5 K,

)	Nixxx Climate: ±0.5 K
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1 =</math> interference frequency</b>	
• Series mode interference (peak value of interference < rated value of input range), min.	40 dB
• Common mode voltage, max.	4 V
• Common mode interference, min.	60 dB
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
• Limit value alarm	Yes; two upper and two lower limit values in each case
<b>Diagnoses</b>	
• Monitoring the supply voltage	No
• Wire-break	Yes; Only for 1 ... 5 V, 4 ... 20 mA, R, and RTD
• Short-circuit	No
• Group error	No
• Overflow/underflow	Yes
<b>Diagnostics indication LED</b>	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	No
• Monitoring of the supply voltage (PWR-LED)	No
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
<b>Permissible potential difference</b>	
between the inputs (UCM)	8 V DC
Between the inputs and MANA (UCM)	4 V DC
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C
<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
<b>Dimensions</b>	
Width	35 mm
Height	147 mm
Depth	129 mm
<b>Weights</b>	
Weight, approx.	250 g
<b>last modified:</b>	1/19/2021 