



SIMATIC S7-1500, CM PTP RS232 BA Communication module for Serial connection RS232, Freepoint, 3964 (R), USS, 19200 Kbit/s, 9-pin D-sub connector

General information	
Product type designation	CM PtP RS 232 BA
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> <li>Fast startup</li> </ul>	Yes; I&M 0 Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> <li>STEP 7 configurable/integrated from version</li> <li>PROFIBUS from GSD version/GSD revision</li> <li>PROFINET from GSD version/GSD revision</li> </ul>	V12 / V12 V5.5 SP2 with GSD file - / - V2.3
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Design of the power supply	system power supply
Input current	
Current consumption (rated value)	50 mA; From the backplane bus
Power	
Power available from the backplane bus	0.75 W
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Inputs</li> </ul>	8 byte
Interface types	
RS 232	
<ul style="list-style-type: none"> <li>Transmission rate, max.</li> <li>Cable length, max.</li> <li>RS 232 auxiliary signals</li> </ul>	19.2 kbit/s 15 m RTS, CTS, DTR, DSR, RI, DCD
Protocols	
Integrated protocols	
Freepoint	
<ul style="list-style-type: none"> <li>Telegram length, max.</li> <li>Bits per character</li> <li>Number of stop bits</li> <li>Parity</li> </ul>	1 kbyte 7 or 8 1 or 2 bit None, even, odd, always 1, always 0, any
3964 (R)	
<ul style="list-style-type: none"> <li>Telegram length, max.</li> <li>Bits per character</li> <li>Number of stop bits</li> </ul>	1 kbyte 7 or 8 1 or 2 bit

— Parity	None, even, odd, always 1, always 0, any
<b>Telegram buffer</b>	
• Buffer memory for telegrams	2 kbyte
• Number of telegrams which can be buffered	255
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
• Hardware interrupt	No
<b>Diagnoses</b>	
• Wire-break	Yes
<b>Diagnostics indication LED</b>	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Receive RxD	Yes; Yellow LED
• Transmit TxD	Yes; Yellow LED
<b>Potential separation</b>	
between backplane bus and interface	Yes
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C
<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200MP system manual
<b>Decentralized operation</b>	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1500	Yes
to standard PROFINET controller	Yes
<b>Dimensions</b>	
Width	35 mm
Height	147 mm
Depth	127 mm
<b>Weights</b>	
Weight, approx.	0.22 kg
<b>last modified:</b>	11/3/2021 