



PB BUS CONNECTOR WITH AXIAL CABLE OUTLET
 F.INDUSTR. PC,
 SIMATIC OP, OLM;
 TRANSMISSION RATE 12 MBIT/S;
 TERMINATING RESISTOR WITH SEPAR. FUNCTION,
 METAL HOUSING

[nicht versorgt: PMD_ABS675_001_000]

-

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

-

2

- [nicht versorgt - für Netzkomponenten und Endgeräte]

1

Design of the electrical connection / [nicht versorgt - FastConnect]

No

Mechanical data

material / of the housing

metal

Design, dimensions and weight

Width

15 mm

Height

57 mm

Depth

39 mm

net weight

100 g

Permitted ambient conditions

Ambient temperature

- during the operating phase
- during storage
- during transport

0 °C ... 60 °C

-25 °C ... 80 °C

-25 °C ... 80 °C

Relative humidity / at 25 °C / without condensation / during the operating phase / maximum

75 %

Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [nicht versorgt - siliconfrei]	Yes
Composant produit	
• [nicht versorgt - PG-Anschlussbuchse]	No
• décharge de traction	Yes
Standards, specifications, approvals	
[nicht versorgt: PMD_ABS586_001_000]	
•	Yes
• UL-registration	No
letzte Änderung:	May 20, 2011