



PB FC RS 485 PLUG 180,
PB-PLUG WITH FASTCONNECT CONNECTOR AND
AXIAL CABLE- OUTLET F. INDUSTRY PC,
SIMATIC OP, OLM,
TRANSMISSION RATE: 12 MBIT/S,
TERMINATING RESISTOR WITH SERAR. FUNCTION,
PLASTIC HOUSING

[nicht versorgt: PMD_ABS675_001_000]

-

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

-

2

- [nicht versorgt - für Netzkomponenten und Endgeräte]

1

Design of the electrical connection / [nicht versorgt - FastConnect]

Yes

Mechanical data

Material / of the housing

plastic

Design, dimensions and weight

Width

16 mm

Height

62 mm

Depth

34.5 mm

Net weight

40 g

Permitted ambient conditions

Ambient temperature

- during the operating phase
- during storage
- during transport

0 °C ... 60 °C

-25 °C ... 80 °C

-25 °C ... 80 °C

Relative humidity / at 25 °C / without condensation / during the operating phase / maximum

75 %

Product properties, functions, components / general

Product feature / [nicht versorgt - siliconfrei]	Yes
Composant produit	
• [nicht versorgt - PG-Anschlussbuchse]	No
• décharge de traction	Yes

Standards, specifications, approvals

[nicht versorgt: PMD_ABS586_001_000]	
•	Yes
• UL-registration	Yes

letzte Änderung: Jun 14, 2010