SIEMENS

Data sheet

6GK5008-0BA10-1AB2

SCALANCE XB008 Unmanaged Industrial Ethernet Switch for 10/100 Mbit/s for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 8x 10/100 Mbit/s twisted pair ports with RJ45 sockets; Manual available as a download



Product type designation	SCALANCE XB008
Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections	
• for network components or terminal equipment	8; RJ45
Number of 100 Mbit/s SC ports	
• for multimode	0
Interfaces / others	
Number of electrical connections	
for power supply	1
Type of electrical connection	
• for power supply	3-pole terminal block
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	AC/DC
Supply voltage	
• external	24 V

• external / minimum	19.2 V	
• external / maximum	28.8 V	
• at AC	24 V	
Product component / fusing at power supply input	Yes	
Fuse protection type / at input for supply voltage	0.6 A / 60 V	
Consumed current / maximum	0.12 A	
Power loss [W]		
• at DC / at 24 V	2.88 W	
Permitted ambient conditions		
Ambient temperature		
during operation	-10 +60 °C	
during storage	-40 +80 °C	
during transport	-40 +80 °C	
Relative humidity		
• at 25 °C / without condensation / during	95 %	
operation / maximum		
Protection class IP	IP20	
Design, dimensions and weight		
Design	Вох	
Width	45 mm	
Height	100 mm	
Depth	87 mm	
Net weight	0.18 kg	
Mounting type		
• 35 mm DIN rail mounting	Yes	
• wall mounting	Yes	
• S7-1500 rail mounting	No	
Product functions / management, configuration		
Product function		
 multiport mirroring 	No	
• CoS	Yes	
PROFINET conformity class	A	
Product function / switch-managed	No	
Product functions / Redundancy		
Product function		
 Parallel Redundancy Protocol (PRP)/operation 	Yes	
in the PRP-network		
 Parallel Redundancy Protocol 	No	
(PRP)/Redundant Network Access (RNA)		
Standards, specifications, approvals		
Standard		

FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, for FM

GP. IIC, T4

EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc. • for hazardous zone

KEMA 07ATEX0145 X

UL 60950-1, CSA C22.2 No. 60950-1 • for safety / from CSA and UL

EN 61000-6-4 (Class A) • for emitted interference

EN 61000-6-2 • for interference immunity

Standards, specifications, approvals / CE

Certificate of suitability / CE marking

Yes

Yes

Standards, specifications, approvals / miscellaneous

Certificate of suitability EN 61000-6-2, EN 61000-6-4

• C-Tick

 KC approval Yes

Standards, specifications, approvals / product conformity

MTBF 214 y

Accessories

Further Information / Internet Links

Internet-Link

• to website: Selector SIMATIC NET

SELECTION TOOL

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

http://www.siemens.com/snst

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about

product updates as they occur, sign up for a product-specific newsletter. For more information, visit

http://support.automation.siemens.com. (V3.4)

last modified: 10/09/2018