

SCALANCE XC108, Unmanaged IE switch, 8x 10/100 Mbit/s RJ45 ports, LED diagnostics, error-signaling contact with set button, redundant Power supply Manual available as a download



Product type designation	SCALANCE XC108
Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / Integrated	
Number of electrical connections	
<ul style="list-style-type: none"> for network components or terminal equipment 	8; RJ45
Interfaces / other	
Number of electrical connections	
<ul style="list-style-type: none"> for signaling contact 	1
<ul style="list-style-type: none"> for power supply 	1
<ul style="list-style-type: none"> for redundant voltage supply 	1
Type of electrical connection	
<ul style="list-style-type: none"> for signaling contact 	2-pole terminal block
<ul style="list-style-type: none"> for power supply 	4-pole terminal block
Signal inputs/outputs	
Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> at DC / Rated value 	24 V

Operating current / of the signaling contacts	
<ul style="list-style-type: none"> • at DC / maximum 	0.1 A
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
<ul style="list-style-type: none"> • external 	24 V
<ul style="list-style-type: none"> • external / minimum 	9.6 V
<ul style="list-style-type: none"> • external / maximum 	31.2 V
Supply voltage / 1 / Rated value	12 V
<ul style="list-style-type: none"> • Supply voltage / 1 / rated value 	9.6 ... 31.2 V
<ul style="list-style-type: none"> • Type of voltage / 1 / of the supply voltage 	DC
<ul style="list-style-type: none"> • Consumed current / 1 / at rated supply voltage / maximum 	0.25 A
Supply voltage / 2 / Rated value	24 V
<ul style="list-style-type: none"> • Supply voltage / 2 / rated value 	9.6 ... 31.2 V
<ul style="list-style-type: none"> • Type of voltage / 2 / of the supply voltage 	DC
<ul style="list-style-type: none"> • Consumed current / 2 / at rated supply voltage / maximum 	0.125 A
<ul style="list-style-type: none"> • Power loss [W] / 2 / Rated value 	3 W
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	2.5 A / 125 V
Power loss [W]	
<ul style="list-style-type: none"> • at DC / at 24 V 	3 W

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-40 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +85 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +85 °C
Relative humidity	
<ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum 	95 %
Protection class IP	IP20

Design, dimensions and weights

Design	compact
Width	60 mm
Height	147 mm
Depth	125 mm
Net weight	0.85 kg
Material / of the enclosure	Polycarbonate (PC-GF10)
Mounting type	
<ul style="list-style-type: none"> • 35 mm DIN rail mounting 	Yes
<ul style="list-style-type: none"> • wall mounting 	Yes

- S7-300 rail mounting Yes
- S7-1500 rail mounting Yes

Product features, product functions, product components / general

Number of automatically learnable MAC addresses 2048

Product functions / management, configuration, engineering

Product function

- multiport mirroring No
- CoS Yes

Product function / switch-managed No

Product functions / redundancy

Product function

- Parallel Redundancy Protocol (PRP)/operation in the PRP-network Yes
- Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) No

Standards, specifications, approvals

Standard

- for hazardous zone EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010
- for safety / from CSA and UL UL 60950-1, CSA C22.2 No. 60950-1
- for hazardous zone / from CSA and UL UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T..., Class 1 / Zone 2 / Group IIC / T..
- for emitted interference EN 61000-6-4 (Class B)

Standards, specifications, approvals / CE

Certificate of suitability / CE marking Yes

Standards, specifications, approvals / other

Laser protection class LED Class 1

Certificate of suitability EN 61000-6-2, EN 61000-6-4

- C-Tick Yes
- E1 approval Yes
- EC declaration of conformity EN 61010, IEC 61010-1, UL 61010A-1 Yes
- KC approval Yes

Standards, specifications, approvals / marine classification

Marine classification association

- American Bureau of Shipping Europe Ltd. (ABS) Yes
- Bureau Veritas (BV) Yes
- DNV GL Yes

- Korean Register of Shipping (KRS)
- Lloyds Register of Shipping (LRS)
- Polski Rejestr Statkow (PRS)
- Royal Institution of Naval Architects (RINA)

Yes
Yes
Yes
Yes

Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>
<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

05/13/2020