

Product type designation

CP 443-1

SIMATIC NET CP 443-1 2 X 10/100 MBIT/S (IE SWITCH); RJ 45 PORTS; ISO; TCP; UDP; PROFINET-IO CONTROLLER; S7-COMMUNICATION; OPEN COMMUNICATION (SEND/RECEIVE); S7-ROUTING; IP-CONFIGURATION VIA DHCP/BLOCK; IP ACCESS CONTROL LIST; TIME-SYNCHRONISATION; EXTENDED WEB-DIAGNOSIS; FAST STARTUP; PROFIENERGY SUPPORT



Transmission rate

Transfer rate	
<ul style="list-style-type: none"> at the 1st interface 	10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet	2
Number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet 	2
Type of electrical connection	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet 	RJ45 port
design of the removable storage / C-PLUG	No

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	5 V
Relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> at 5 V 	5 %
Consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 5 V / typical 	1.4 A

Power loss [W]	7.25 W
----------------	--------

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.7 kg

Product properties, functions, components / general

Number of units	
<ul style="list-style-type: none"> per CPU / maximum 	14
<ul style="list-style-type: none"> Note 	max. 4 as PN IO ctrl.

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
Amount of data	
<ul style="list-style-type: none"> as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	2 Kibyte
Number of possible connections / for open communication	
<ul style="list-style-type: none"> by means of T blocks / maximum 	64
Amount of data	
<ul style="list-style-type: none"> as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum 	1452 byte

Performance data / S7 communication

Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> • maximum 	128
<ul style="list-style-type: none"> • with PG connections / maximum 	2
<ul style="list-style-type: none"> • Note 	when using several CPUs

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	128
---	-----

Performance data / PROFINET communication / as PN IO-Controller

Product function / PROFINET IO controller	Yes
Number of PN IO devices / on PROFINET IO controller / usable / total	128
Number of PN IO IRT devices / on PROFINET IO controller / usable	64
Number of external PN IO lines / with PROFINET / per rack	4
Amount of data	
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	4 Kibyte
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	4 Kibyte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 	240 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum 	240 byte
Product function / MIB support	Yes
Protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • DCP 	Yes
<ul style="list-style-type: none"> • LLDP 	Yes
Configuration software	
<ul style="list-style-type: none"> • required 	STEP 7 V5.5 SP3 or higher / STEP 7 Professional V12 (TIA Portal) or higher

Product functions / Diagnosis

Product function / Web-based diagnostics	Yes
--	-----

Product functions / switch

Product feature / Switch	Yes
Product function	
• switch-managed	No
• with IRT / PROFINET IO switch	Yes
• Configuration with STEP 7	Yes

Product functions / Redundancy

Product function	
• Ring redundancy	Yes
• Redundancy manager	Yes
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes

Product functions / Security

Product function	
• password protection for Web applications	No
• ACL - IP-based	Yes
• ACL - IP-based for PLC/routing	No
• switch-off of non-required services	Yes
• Blocking of communication via physical ports	Yes
• log file for unauthorized access	No

Product functions / Time

Product function / SICLOCK support	Yes
Product function / pass on time synchronization	Yes
Protocol / is supported	
• NTP	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/12/2016