



COMMUNICATIONS MODULE CM 1542-1 FOR CONNECTING S7-1500 TO PROFINET AS IO-CONTROLLER: TCP/IP, ISO-ON-TCP, UDP, S7-COMMUNICATION, IP-BROADCAST/ MULTICAST, SNMPV1, DHCP, CLOCK SYNCHRONISATION VIA NTP, 2XRJ45 (10/100 MBIT)

Transmission rate

Transfer rate	
<ul style="list-style-type: none"> at the 1st interface 	10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet 	2
Design of the electrical connection	
<ul style="list-style-type: none"> at the 1st interface / acc. to Industrial Ethernet 	RJ45 port

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	15 V
Relative symmetrical tolerance / for DC	
<ul style="list-style-type: none"> at 15 V 	3 %
Consumed current	
<ul style="list-style-type: none"> from backplane bus / for DC / at 15 V / typical 	0.22 A
Active power loss	3.3 W

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> for vertical installation / during operation 	0 ... 40 °C
<ul style="list-style-type: none"> for horizontally arranged busbars / during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C

Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1500 single width
Width	35 mm
Height	142 mm
Depth	129 mm
Net weight	0.4 kg
Mounting type <ul style="list-style-type: none"> • S7-1500 rail mounting 	Yes

Product properties, functions, components / general

Number of units <ul style="list-style-type: none"> • per CPU / maximum • Note 	8 depending on CPU type
---	----------------------------

Performance data / open communication

Number of possible connections / for open communication <ul style="list-style-type: none"> • by means of T blocks / maximum 	64; depending on the system upper limit
Amount of data <ul style="list-style-type: none"> • as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum 	65536 byte
Number of Multicast stations	6

Performance data / S7 communication

Number of possible connections / for S7 communication <ul style="list-style-type: none"> • maximum • Note 	64 depending on the system upper limit
---	---

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	64
---	----

Performance data / PROFINET communication / as PN IO-Controller

Product function / PROFINET IO controller	Yes
Number of PN IO devices / on PROFINET IO controller / usable / total	128
Number of PN IO IRT devices / on PROFINET IO controller / usable	64
Number of external PN IO lines / with PROFINET / per rack	10
Amount of data	

• as user data for input variables / as PROFINET IO controller / maximum	8 Kibyte
• as user data for input variables / as PROFINET IO controller / maximum	8 Kibyte
• as user data for input variables per PN IO device / as PROFINET IO controller / maximum	1433 byte
• as user data for output variables per PN IO device / as PROFINET IO controller / maximum	1433 byte
• as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum	256 byte
• as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum	256 byte

Performance data / telecontrol

Protocol / is supported	
• TCP/IP	Yes

Product functions / management, configuration

Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• DCP	Yes
• LLDP	Yes
Configuration software	
• required	STEP 7 Professional V13 (TIA Portal) or higher
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes

Product functions / Diagnosis

Product function / Web-based diagnostics	Yes; yes, via S7-1500 CPU
--	---------------------------

Product functions / switch

Product feature / Switch	Yes
Product function	
• switch-managed	No
• with IRT / PROFINET IO switch	Yes
• Configuration with STEP 7	Yes

Product functions / Redundancy

Product function	
• Ring redundancy	Yes
• Redundancy manager	Yes

Product functions / Security

Product function

- | | |
|--|-----|
| • switch-off of non-required services | Yes |
| • Blocking of communication via physical ports | No |
| • log file for unauthorized access | No |

Product functions / Time

- | | |
|---|-----|
| Product function / SICLOCK support | Yes |
| Product function / pass on time synchronization | Yes |
| Protocol / is supported / NTP | Yes |

Further Information / Internet Links

Internet-Link

- | | |
|---|---|
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/automation/net/catalog |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

23.02.2015