

# SIEMENS

## Product data sheet

**6SE6420-2AB21-5BA1**

product name

Micromaster 4



MICROMASTER 4 Familie

MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ  
 CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.5 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20  
 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP

Input voltage	230 V
Output voltage / maximum	240 V
Output voltage / minimum	0 V
<b>Line frequency rated value 50 Hz</b>	-
<b>Line frequency rated value 60 Hz</b>	-
power factor	0.95
efficiency eta	96
<b>pulse rate factory setting</b>	-
Design	B
Protection class IP	MICROMASTER 440
environmental conditions / Ambient temperature in operation	-10° to +50°C
filter / [nicht versorgt - Klasse A] / [nicht versorgt - 1AC]	FALSE
type / of control	FCC, Linear - V/f

---

Height	0.202 m
Width	0.149 m
Depth	0.172 m
weight	3 kg
<b>letzte Änderung:</b>	Feb 14, 2011