

SIEMENS

Product data sheet

6SE6440-2AD33-7EA1

product name

Micromaster 4



MICROMASTER 4 Familie

MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ
 CONSTANT TORQUE POWER 37 KW OVERLOAD 150% 60 S,
 200% 3 S SQUARED TORQUE POWER 45 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT
 TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP

Input voltage	400 V
Output voltage / maximum	480 V
Output voltage / minimum	0 V
Line frequency rated value 50 Hz	-
Line frequency rated value 60 Hz	-
power factor	0.95
Efficiency eta	96
Pulse rate factory setting	-
Design	E
Protection class IP	MICROMASTER 440
Environmental conditions / Ambient temperature in operation	-10° to +40°C (VT) / 50°C (CT)
filter / [nicht versorgt - Klasse A] / [nicht versorgt - 1AC]	FALSE
type / of control	Vector, FCC, Linear - V/f

Height	0.65 m
Width	0.275 m
Depth	0.245 m
weight	22 kg
letzte Änderung:	Aug 8, 2011