



Figure similar

MLFB-Ordering data

6SL3040-1LA00-0AA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Inputs / outputs

Digital inputs

Number of potential-free inputs	11
Voltage	-3 ... +30 V
Low level	-3 ... +5 V
High level	15 ... 30 V
Power consumption at 24 V DC, typ.	3.5 mA
Delay time L→H, typ.	50 μs
Delay time H→L, typ.	150 μs

Analog inputs

Number ¹⁾	1
As voltage input	
Voltage	-10 ... +10 V
Resolution	12 bit + sign (with respect to the maximum range that can be resolved -11 ... +11 V)
R _i	>100 kΩ

As current input

Current	-20 ... +20 mA
Resolution	11 bit + sign (with respect to -22 ... 22 mA); Maximum range that can be resolved -44 ... +44 mA)
R _i	>250 Ω

Digital I/O

Number of bidirectional, not potential-free inputs	8
--	---

As input

Voltage	-3 ... +30 V
Low level	-3 ... +5 V
High level	15 ... 30 V
Power consumption at 24 V DC, typ.	3.5 mA
Delay time L→H	5 μs
Delay time H→L	50 μs

As output

Voltage	DC 24 V
Load current per digital output, max.	500 mA
Delay time L→H, typ./ max.	150 μs / 400 μs
Delay time H→L, typ./ max.	75 μs / 100 μs

1) The analog input can be switched between current and voltage input.



Figure similar

MLFB-Ordering data

6SL3040-1LA00-0AA0

Electrical data		Ambient conditions	
Electronics power supply	DC 24 V (20.4 ... 28.8 V)	Installation altitude	2000 m (6561.68 ft)
Max. power consumption ²⁾	0.80 A	Ambient temperature during	
Power loss, max.	20 W	Operation	0 ... 55 °C (32 ... 131 °F)
Mechanical data		Storage	-25 ... 55 °C (-13 ... 131 °F)
Dimensions		Transport	-40 ... 70 °C (-40 ... 158 °F)
Width	73 mm (2.87 in)	Relative humidity	
Height	191 mm (7.52 in)	Transport, max.	95 %
Depth	75 mm (2.95 in)		at 40 °C (104 °F)
Net weight	0.95 kg (2.09 lb)	Connections	
On-board encoder interface		PE connection	1 (M5 screw)
max. load current at 24 V encoder supply	0.35 A	DRIVE-CLiQ	1
max. load current at 5 V encoder supply	0.35 A	PROFINET	--
Encoder frequency, max.	300 kHz	PROFIBUS	1
SSI baudrate	100 ... 1000 kBaud	RS232	--
SSI absolute position resolution	30 bit	Ethernet	1
Line length, max.		Temperature sensor	1
TTL encoder	100 m (328.08 ft)	24 V	1
HTL encoder unipolar signal	100 m (328.04 ft)	Measuring sockets	3
HTL encoder bipolar signal	300 m (984.25 ft)	Number of slots	
SSI encoder	100 m (328.08 ft)	Flash card	1
		Communication	
		Communication	Profibus DP
		Standards	
		Compliance with standards	CE, KC, cULus, EAC, C-Tick (RCM)

²⁾ without taking into account digital outputs. Option slot extension, DRIVE-CLiQ supply and Power Module PM340