

# SIEMENS

## Product data sheet

**6SL3211-0AB23-0UA1**

product name	SINAMICS G110
Design	C
input / [nicht versorgt - Bemessungsspannung] / [nicht versorgt - AC]	230 V
Input voltage / minimum	200 V
Output voltage / minimum	240 V
Input voltage / maximum	240 V
rated output / kilowatt (kW)	3 kW
Rated Power / in Kilowatt (kW) / High Overload (HO)	3 kW
rated output / in Horse Power (HP)	4 hp
	35.6 A
	13.6 A
efficiency eta	95
	unfiltered
type / [nicht versorgt - der Überlastbarkeit]	150% for 60s within 300s, after that 85% for 240s within 300s
type / of control	linear V/f, multipoint V/f, quadratic V/f
Number / [nicht versorgt - PTC-Eingänge]	0
Number / analog inputs	1
type / [nicht versorgt - Bremschopper vorhanden]	No
Number / digital inputs	3
Number / analog outputs	0
Number / [nicht versorgt - Relaisausgänge]	1
Type of cooling	ventilation external
cooling method / [nicht versorgt - Kühlkörper]	Heat sink
Protection class IP	IP 20
environmental conditions / Ambient temperature in operation	-10 to +40°C
Depth	0.152 m

Height	0.181 m
Width	0.184 m
power factor	0.95
weight	2 kg
	0.91
Installation filter	No
filter / [nicht versorgt - Klasse A] / [nicht versorgt - 1AC]	FALSE
filter / [nicht versorgt - Klasse B] / [nicht versorgt - 1AC]	FALSE
filter / [nicht versorgt - Klasse B] / [nicht versorgt - 1AC] / [nicht versorgt - niedriger Ableitstrom]	FALSE
<b>letzte Änderung:</b>	May 16, 2011