

Product type designation

Product description

SIMATIC NET Antenna Connection Cable N-Connect Male/ Male

Connecting cable for SIMATIC NET antennas, preassembled

SIMATIC NET N-CONNECT MALE/ MALE FLEXIBLE

CONNECTION CABLE PRE-ASSEMBLED; LENGTH 5M FLEXIBLE

CONNECTION CABLE E. G. FOR 2 RCOAX SEGMENTS



Suitability for use	Flexible connecting cable for connecting an antenna or RCoax cable to a SCALANCE M/W
Cable length	5 m
Electrical data	
Number of electrical connections	2
Type of electrical connection	N-Connect/N-Connect male/male
Transmission frequency	0 ... 6000 MHz
Damping ratio per length	
• at 2.4 GHz / typical	0.53 dB/m
• at 5.2 GHz / typical	0.83 dB/m
• at 5.85 GHz / typical	0.89 dB/m
Return loss / minimum	23 dB
Impedance	
• Rated value	50 Ω
Capacity per length / at 1 kHz	82 pF/m
Relative speed	82 %
Mechanical data	

Design of the shield	Braided shield made of tin-plated copper wires
Outer diameter	
<ul style="list-style-type: none"> • of inner conductor • of dielectric • of cable sheath 	1.4 mm 3.8 mm 6.3 mm
Symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
Thickness / of cable sheath	0.76 mm
Material	
<ul style="list-style-type: none"> • of inner conductor • of dielectric • of cable sheath 	Cu polyethylene foam FRNC
Color	
<ul style="list-style-type: none"> • of cable sheath 	pastel turquoise
Bending radius	
<ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible 	32 mm 45 mm
Tensile load / maximum	80 N
Weight per length	75 kg/km

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	-40 ... +80 °C -40 ... +80 °C -40 ... +80 °C -25 ... +80 °C
Chemical resistance	
<ul style="list-style-type: none"> • to mineral oil 	conditional resistance
Radiological resistance / to UV radiation	resistant
Protection class IP	IP68; when plugged in

Product properties, functions, components / general

Product property	
<ul style="list-style-type: none"> • halogen-free • silicon-free 	Yes Yes

Standards, specifications, approvals

Certificate of suitability	
<ul style="list-style-type: none"> • RoHS conformity 	Yes

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication 	http://www.siemens.com/snst http://www.siemens.com/simatic-net

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

08.10.2015