

SENTRON, measuring device, 7KM PAC3100, LCD, L-L: 480 V, L-N: 277 V, 3-phase, Modbus RTU, active/reactive energy, class 1 acc. to IEC 61557-12 & 62053-21, wide-range power sup. unit AC/DC, screw terminals



Model	
Product brand name	SENTRON
Product designation	7KM PAC3100
Design of the product	basic
Product type designation	Measuring instrument
Type of measured value detection	complete
Design of the power supply	Wide-range power supply
General technical data	
Cutout width	92 mm
Cutout height	92 mm
Size of Power Monitoring Device / company-specific	size 96
Operating mode for measured value detection	
<ul style="list-style-type: none"> • automatic line frequency detection 	Yes
<ul style="list-style-type: none"> • set at 50 Hz 	No
<ul style="list-style-type: none"> • set to 60 Hz 	No
Pulse duration	
<ul style="list-style-type: none"> • initial value 	30 ms
<ul style="list-style-type: none"> • Full-scale value 	500 ms

Voltage curve	Sinusoidal or distorted
Measurable line frequency / initial value	45 Hz
Measurable line frequency / Full-scale value	65 Hz
Measuring procedure / for voltage measurement	TRMS
Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	P

Supply voltage

Supply voltage frequency / rated value	
<ul style="list-style-type: none"> • minimum • maximum 	45 Hz 65 Hz
Type of voltage / of the supply voltage	AC/DC
Measuring category / for supply voltage	CATIII
Apparent power consumption	
<ul style="list-style-type: none"> • without expansion module / typical 	10 V·A
Relative symmetrical tolerance / of the supply voltage	10 %

Protection class

Protection class IP	
<ul style="list-style-type: none"> • on the front • Rear side 	IP65 IP20
Operating resource protection class / when installed	II

Suitability

Suitability for operation	Installation in stationary control panels in closed rooms
Adjustable time period / minimum	10 ms

Product function

Product function	
<ul style="list-style-type: none"> • Illuminance of display backlighting adjustable • Time-controlled reduction of the illuminance of display backlighting possible • reactive power measurement • frequency measurement • pulse measurement • Display contrast adjustable • voltage measurement • Current measurement • active power measurement 	No Yes Yes Yes No Yes Yes Yes Yes

Display and operation

Design of the display	LCD
Number of keys	4
Color / of the background of the display	white
National language / on the display screen / is supported	ger, en, fr, spa, ita, por, tur, chi

Product function / Display can be inverted (positive <=> negative mode)	Yes
Horizontal image resolution	128
Vertical screen resolution	96
Refresh time / on display	
• minimum	0.33 s
• maximum	3 s

Communication

Protocol	
• is supported	Modbus RTU
Transfer rate	
• minimum	4.8 kbit/s
• maximum	38.4 kbit/s

Fault limits

Reference condition / for metering accuracy	according to IEC61557-12 (K55)
Formula for relative total measurement inaccuracy	
• for measured variable reactive energy	Class 3 according to IEC61557-12 and IEC62053-23
• for measured variable reactive power	+/- 3 %
• for measured variable output	+/- 1.0 %
• for measured variable output factor	+/- 1 %
• for measured variable voltage	+/- 1.0 %
• for measured variable current	+/- 1.0 %
• for measured variable active energy	Class 1 according to IEC 61557-12 and IEC62053-21
• for measured variable active power	+/- 1 %

Inputs Outputs

Input voltage / at digital input	
• at DC / maximum	30 V
Number of digital outputs	2
Number of digital inputs	2
Digital output version	switching or pulse output function
Design of the switching input	Self-supplied
Type of switching output	bidirectional
Type of electrical connection	
• at the digital inputs	screw-type terminals
• at the digital outputs	screw-type terminals
Input current / at digital input	
• initial value for signal<1>-recognition	2.5 mA
• Full-scale value for signal<0> recognition	0.5 mA
• for signal <1> / minimum	2.5 mA
Output current	
• at digital output / with signal <0> / maximum	0.2 mA

<ul style="list-style-type: none"> • at digital output / for signal <1> / minimum 	10 mA
<ul style="list-style-type: none"> • at digital output / for signal <1> / maximum 	27 mA
<ul style="list-style-type: none"> • at the digital outputs / at DC / limited to 100 ms / maximum 	130 mA
<ul style="list-style-type: none"> • at the digital outputs / at DC / maximum 	30 mA
Output delay / at digital output	
<ul style="list-style-type: none"> • for signal <0> to <1> / maximum 	5 ms
<ul style="list-style-type: none"> • for signal <1> to <0> / maximum 	5 ms
Operating conditions for digital inputs / external voltage supply	No
Operating voltage / as output voltage / at DC / maximum permissible	30 V
Property of the output / Short-circuit proof	Yes
Input delay time / at digital input	
<ul style="list-style-type: none"> • for signal <0> to <1> / maximum 	30 ms
<ul style="list-style-type: none"> • for signal <1> to <0> / maximum 	30 ms
Internal resistance / at the digital outputs	55 Ω
Load resistance / at digital input	
<ul style="list-style-type: none"> • initial value for signal<0>-recognition 	100 000 Ω
<ul style="list-style-type: none"> • Full-scale value for signal<1> recognition 	1 000 Ω
Measuring category / for digital signals	CATI
Switching frequency / at digital output / maximum	17 Hz

Measuring inputs

Outer conductors and neutral conductors internal resistance / for voltage measurement	0.84 MΩ
Measurable supply voltage	
<ul style="list-style-type: none"> • between (PE)N and L / at AC / minimum 	11.5 V
<ul style="list-style-type: none"> • between (PE)N and L / at AC / maximum 	277 V
<ul style="list-style-type: none"> • between (PE)N and L / at AC / maximum rated value 	277 V
<ul style="list-style-type: none"> • between the outer conductors / at AC / minimum 	20 V
<ul style="list-style-type: none"> • between the outer conductors / at AC / maximum 	480 V
<ul style="list-style-type: none"> • between the outer conductors / at AC / maximum rated value 	480 V
Voltage measuring range extension / with external voltage transformers	Yes
Current measuring range extension / with external current transformers	Yes
Measuring category / for voltage measurement	CATIII
Supply voltage / between the outer conductors / at AC / maximum permissible	576 V

Consumed active power / for current measurement / per phase	500 mW
Continuous current / at AC / maximum permissible	10 A
Measuring category / for current measurement	CATIII
Zero-point suppression / for current measurement	10 mA
<ul style="list-style-type: none"> • for neutral conductor current 	45 mA
Relative measurable current / at AC	
<ul style="list-style-type: none"> • minimum 	0.2 %
<ul style="list-style-type: none"> • maximum 	120 %
Apparent power consumption / for current measurement	
<ul style="list-style-type: none"> • with measuring range 5 A / per phase 	0.5 V·A
Measuring procedure / for current measurement	TRMS
Measurable current / 1 / at AC / Rated value	5 A

Connections

Type of connectable conductor cross-sections	
<ul style="list-style-type: none"> • at the digital inputs / at AWG conductors / solid 	1x 24 ... 12
<ul style="list-style-type: none"> • at the digital inputs / solid 	1x (0.2 ... 2.5 mm ²), 2x (0.2 ... 1.0 mm ²)
<ul style="list-style-type: none"> • at the digital inputs / finely stranded / with core end processing 	1x (0.25 ... 2.5 mm ²), 2x (0.25 ... 1.0 mm ²)
<ul style="list-style-type: none"> • at the digital outputs / at AWG conductors / solid 	1x 24 ... 12
<ul style="list-style-type: none"> • at the digital outputs / solid 	1x (0.2 ... 2.5 mm ²), 2x (0.2 ... 1.0 mm ²)
<ul style="list-style-type: none"> • at the digital outputs / finely stranded / with core end processing 	1x (0.25 ... 2.5 mm ²), 2x (0.25 ... 1.0 mm ²)
<ul style="list-style-type: none"> • at the inputs for supply voltage / at AWG conductors / solid 	2x 20 to 14
<ul style="list-style-type: none"> • at the inputs for supply voltage / solid 	1x (0.5 ... 4 mm ²), 2x (0.5 ... 2.5 mm ²)
<ul style="list-style-type: none"> • at the inputs for supply voltage / finely stranded / with core end processing 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.5 mm ²)
<ul style="list-style-type: none"> • at the measurement inputs for voltage / at AWG conductors / solid 	2x 20 to 14
<ul style="list-style-type: none"> • at the measurement inputs for voltage / solid 	1x (0.5 ... 4 mm ²), 2x (0.5 ... 2.5 mm ²)
<ul style="list-style-type: none"> • at the measurement inputs for voltage / finely stranded / with core end processing 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.5 mm ²)
<ul style="list-style-type: none"> • at the measurement inputs for current / at AWG conductors / solid 	2x 20 to 14
<ul style="list-style-type: none"> • at the measurement inputs for current / solid 	1x (0.5 ... 4 mm ²), 2x (0.5 ... 2.5 mm ²)
<ul style="list-style-type: none"> • at the measurement inputs for current / finely stranded / with core end processing 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.5 mm ²)
Type of electrical connection	
<ul style="list-style-type: none"> • at the inputs for supply voltage 	screw-type terminals
<ul style="list-style-type: none"> • at the measurement inputs for voltage 	screw-type terminals

- at the measurement inputs for current

screw-type terminals

Mechanical Design

Height	96 mm
Height / of the display	54 mm
Width	96 mm
Width	
• of the display	72 mm
Depth	56 mm
Mounting position	vertical
Installation depth	51 mm
Mounting type / panel mounting	Yes
Material thickness / of the control panel	
• maximum	4 mm
Net weight	469 g

Environmental conditions

Degree of pollution	2
Installation altitude / at height above sea level / maximum	2 000 m
Standard	
• for EMC for industrial sector	IEC 61000-6-2 respectively IEC 61326-1:2005, table 2
• for EMC against unloading	IEC 61000-4-2
• for EMC against high frequency fields	IEC 61000-4-3
• for EMC against conducted disturbance variables via HF fields	IEC 61000-4-6
• for EMC against magnetic fields with power engineering frequencies	IEC 61000-4-8
• for EMC against quick, transient electrical disturbances	IEC 61000-4-4
• for EMC against voltage drops and interruptions	IEC 61000-4-11
• for EMC against surge voltages	IEC 61000-4-5
• for pulse emitter	according to IEC62053-31
• for cyclic, environmental damp heat check	IEC 60068-2-30
• for environmental coldness check	IEC 60068-2-1
• for environmental dry heat check	IEC 60068-2-2
Relative humidity / at 25 °C / without condensation / during operation	
• minimum	5 %
• maximum	95 %
Ambient temperature	
• during operation / minimum	-10 °C
• during operation / maximum	55 °C

- during storage / minimum
- during storage / maximum

-25 °C

70 °C

Certificates

Certificate of suitability	
<ul style="list-style-type: none"> • as EC declaration of conformity • as approval for Canada • as approval for USA • Approval Australia 	<p>IEC 61010-1: 2001 (2nd Ed.) with Corr. 1, EN 61010-1: 2001 (2nd Ed.) and DIN EN 61010-1:2002 with "Berichtigung 1"</p> <p>UL 61010-1, 2nd Ed. CAN/CSA-C22.2 NO. 61010-1-04</p> <p>UL 61010-1, 2nd Ed. CAN/CSA-C22.2 NO. 61010-1-04</p> <p>Yes</p>
Reference code / acc. to DIN EN 61346-2	P

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KM3133-0BA00-3AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KM3133-0BA00-3AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KM3133-0BA00-3AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



