SIEMENS

Product data sheet

3RT1617-1AB03



CAPACITOR SW. CONTACTOR, AC-6, 12.5KVAR/400V, 24V, 50/60HZ, 3-POLE, SIZE S00

Number of poles		3
Type of mounting		screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
series installation		Yes
Operating reactive power / at AC-6b		
• at 230 V / at 50/60 Hz / rated value		
• minimum	kvar	3
• minimum	kvar	7.5
• at 400 V / at 50/60 Hz / rated value		
• minimum	kvar	5
• maximum	kvar	12.5
• at 500 V / at 50/60 Hz / rated value		
• minimum	kvar	7.5
• maximum	kvar	15
• at 690 V / at 50/60 Hz / rated value		
• minimum	kvar	10
• maximum	kvar	21
tem designation / according to DIN EN 61346-2		Q
tem designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		К

Protection class IP		IP20	
Width	mm	45	
Height	mm	83	
Depth	mm	110	
ambient temperature	_		
 during the operating phase 	°C	-25 60	
Control circuit:			
type of voltage		AC	
Control supply voltage	_		
• at 50 Hz / at AC / rated value / minimum	V	24	
• at 50 Hz / at AC / rated value / maximum	V	24	
• at 60 Hz / at AC / rated value / minimum	V	24	
• at 60 Hz / at AC / rated value / maximum	V	24	
Supply voltage frequency / for auxiliary and control current circuit / rated value	_		
• minimum	Hz	50	
• maximum	Hz	60	
Main circuit:			
Number of NC contacts / for main contacts		0	
Number of NO contacts / for main contacts	_	3	
Operating current / at AC-1 / at 400 V / rated value	А	18	
Auxiliary circuit:			
Identification number and letter for switching elements		11	
Number of NO contacts / for auxiliary contacts		1	
Number of NC contacts / for auxiliary contacts		1	
Connection type:			
Design of the electrical connection / for main current circuit		screw-type terminals	
Design of the electrical connection / for auxiliary and control current circuit		screw-type terminals	
Certificates/annrovals:			

Certificates/approvals:

General Produc	t Approval		Functional Safety / Safety of Machinery	Test Certificates	
(SP)	ROSTEST	(U)L	<u>SUVA</u>	Manufacturer	
Shipping Appro	oval				
ABS	Ĵ Å	GEL COPERATING 24/7	Llovds Register	RINA	
other					
Manufacturer	other				
http://www.siemer CAx-Online-Gene http://www.siemer Service&Support	ns.com/cax t (Manuals, Certificate				
		dimension drawings, 3E db/cax_en.aspx?mlfb=3F) models, device circuit di RT1617-1AB03	agrams,)	

last change:

May 16, 2011