



Figure similar

### Ordering data

6SL3224-0BE13-7UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
<b>Input</b>		Power factor $\lambda$	0.85
Number of phases	3 AC	Offset factor $\cos \varphi$	0.95
Line voltage	380 ... 480 V $\pm 10\%$	Efficiency $\eta$	0.97
Line frequency	47 ... 63 Hz	Sound pressure level (1m)	45 dB
Rated current with line reactor	1.40 A	Power loss	0.09 kW
Rated current without line reactor	1.70 A	<b>Ambient conditions</b>	
<b>Output</b>		Cooling	Internal air cooling
Number of phases	3 AC	Cooling air requirement	0.005 m <sup>3</sup> /s
Rated voltage	400 V	Installation altitude	1000 m
Rated power (LO)	0.37 kW / 0.50 hp	<b>Ambient temperature</b>	
Rated power (HO)	0.37 kW / 0.50 hp	Operation LO	0 ... 40 °C (32 ... 104 °F)
Rated current (LO)	1.30 A	Operation HO	0 ... 50 °C (32 ... 122 °F)
Rated current (HO)	1.30 A	Transport	-40 ... 70 °C (-40 ... 158 °F)
Max. output current	2.60 A	Storage	-25 ... 55 °C (-13 ... 131 °F)
Pulse frequency	4 kHz	<b>Relative humidity</b>	
Output frequency for vector control	0 ... 200 Hz	Max. operation	95 % RH, condensation not permitted
Output frequency for V/f control	0 ... 550 Hz		

### Overload capability

#### Low Overload (LO)

1.1 × output current rating (i.e., 110 % overload) for 57 s with a cycle time of 300 s  
 1.5 × output current rating (i.e., 150 % overload) for 3 s with a cycle time of 300 s

#### High Overload (HO)

1.5 × output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s  
 2 × output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s



Figure similar

Ordering data

6SL3224-0BE13-7UA0

### Mechanical data

Degree of protection	IP20
Size	FSA
Net weight	1.10 kg
Width	73.0 mm
Height	173.0 mm
Depth	145.0 mm

### Connections

#### Line side

Version	screw-type terminal
Conductor cross-section	1.00 ... 2.50 mm <sup>2</sup>

#### Motor end

Version	Screw-type terminals
Conductor cross-section	1.00 ... 2.50 mm <sup>2</sup>

#### DC link (for braking resistor)

Conductor cross-section	1.00 ... 2.50 mm <sup>2</sup>
-------------------------	-------------------------------

#### Max. motor cable length

Shielded	50 m
Unshielded	100 m

### Standards

Compliance with standards	UL, cUL, CE, C-Tick (RCM), SEMI F47
CE marking	According to low-voltage directive 2006/95/EC