

Small-scale distributors

## AK-F 56



### AK-F 56

Small-scale distributors

CUSTOMIZABLE

Productnumber: 73355601

Dimensions: 315 x 750 x 155 mm

Small-scale distributors, protection class IP65, 4 Rows, 56 available modules, Flange type, with integrated ventilation elements for reducing the formation of condensation, Rated operational voltage: 400V AC, Rated insulation voltage: 1000V AC, 1500V DC, certified by VDE (DIN EN 60670-1/-24 (VDE 0606-1/-24)), UL-EU (EN 62208), UL-EU (EN 61439-1/-2), UL-EU (EN 61439-1/-3), UL-EU (EN 61439-1 & EN IEC 61439-7), DLG (Ammonia resistance), open top/bottom sides for the use with various flanges or for the combination of several AK-F distributors via combination flange

**PE/N terminal block, consisting of: PE terminal block with 6 screw terminals 2.5-16mm<sup>2</sup> and 21 push-in terminals 0.75-4mm<sup>2</sup>, 4 N-modules (connected with jumper) each with 2 screw terminals 2.5-16mm<sup>2</sup> and 6 push-in terminals 0.75-4mm<sup>2</sup> with operating lever for toolless releasing of the conductors**

**Accessories supplied:**

**Double-membrane seals: 2x M16, 10x M20, 4x M25, 2x M32, 2x M40, sealing plugs, masking and labelling strips**



Reliable - The high protection class (IP65) and the robust, halogen-free design ensure reliable operation even in a tough industrial environment.

## Technical Data

### electrical characteristics

Rated operating voltage AC:	400 V
Rated insulation voltage AC:	1000 V
Rated insulation voltage DC:	1500 V
Protection class:	II
Type of protection:	IP65
vented:	yes
Number of N-potentials:	2
Number of rows:	4
Number of modules:	56
Number of modules per row:	14

### Colours

Base unit colour:	grey
Cover colour:	grey

### Dimensions

Width:	315 mm
Length:	750 mm
Height:	155 mm
Inner length:	730 mm
Inner width:	295 mm
Inner height:	106 mm

### Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	650 °C
Industry quality:	yes

### mechanical properties

Type of fastening:	Surface mounting
Impact strength:	IK08
Sealable:	yes
Cover screw torque:	1.2 Nm
Flange variant:	yes
Stackable:	yes

### Ambient conditions

max. relative humidity 25°C:	90 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C
Installation location:	protected outdoor areas

### Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced
Hinged window material:	Polycarbonate

### Certificates

Test mark:	VDE (DIN EN 60670-1/-24 (VDE 0606-1/-24))
Test mark:	UL-EU (EN 62208)
Test mark:	UL-EU (EN 61439-1/-2)
Test mark:	UL-EU (EN 61439-1/-3)
Test mark:	UL-EU (EN 61439-1 & EN IEC 61439-7)
Test mark:	DLG (Ammonia resistance)

## Accessories

[73382001 - AK3 FL00 - Flange for AK-F](#)

[73382101 - AK3 FL01 - Flange for AK-F](#)

[73382201 - AK3 FL02 - Flange for AK-F](#)

[73382801 - AK3 FL13 - Flange for AK-F](#)

[73382901 - AK3 KFL - Flange for AK-F](#)

[19302601 - KST M25-33 - Combi connector](#)

[70610201 - AK SGA-1 - Lock fittings](#)

[70690201 - AK SGA-2 - Lock fittings](#)

[73381201 - AK3 NS35-14 - Standard rail](#)

[73381301 - AK3 NS35-275 - Standard rail](#)

[73383001 - AK3 KS M50 - Combination cable gland](#)

[73383101 - AK3 KBL - Cable cover](#)

[73383201 - AK3 TW - Partition wall](#)

[73383301 - AK3 ABL-ES - External fixing lugs](#)

[73383401 - AK3 STD - Mounting socket](#)

[79031801 - AK N-SL - Terminal rails](#)

[79080501 - KLS PE 35 - Terminal block](#)

[79090501 - KLS N 35 - Terminal block](#)

[79901201 - AK AS - Masking off strips](#)

[79901301 - AK AS-v - Masking off strips](#)

[79032101 - KLS N 1/14-SL - Plug clamps](#)

[79032201 - KLS PE 1/14-SL - Plug clamps](#)

## Cable gland

