



General ordering data

Order No.	0218660000
Short text for material	SAK 2.5/EN
EAN	4008190010171
Qty	100

Additional technical data

No. of identical terminals	1
Type of connection	screwed
Type of mouting	clipped
Version	Feed-through terminal
Installation advice	TS 35 + TS 32
UL 94 flammability rating of insulation material	V2
Insulating material	PA 66
Colour of insulating material	beige
Operating temperature range	- 50 °C, + 100 °C
Open sides	right
No. of levels	1
No. of terminal strips per level	2
Levels cross-connected internally	No
End plate required	Yes
Explosion-tested version "Ex e"	No
Connection direction	on side

CSA rating data

Voltage CSA	600 V
CSA current	25 A
Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 10

Conductors for clamping (rated connection)

Flexible with ferrule, max. (DIN 46228 pt 1)	4 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm ²
Flexible with ferrule, min. (DIN 46228 pt 1)	0,5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0,5 mm ²
Clamping range, max.	6 mm ²
Clamping range, min.	0,13 mm ²
Clamping screw	M 2.5
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A3
AWG conductor size, max.	3,31 mm ²
AWG conductor size, max.	AWG 12
Stranded, max.	4 mm ²
Stranded, min.	0,5 mm ²
Stripping length	10 mm
Type of connection	Screw connection
No. of connections	2
Tightening torque range	0.4...0.6 Nm
Solid, max.	6 mm ²
Flexible, max.	4 mm ²
AWG conductor size, min. (mm)	0,13 mm ²
AWG conductor size, min.	AWG 22
Connection direction	on side
Flexible, min.	0,5 mm ²
2nd type of connection	screwed
Solid, min.	0,5 mm ²
Twin wire-end ferrule, min.	0,50 mm ²
Twin wire-end ferrule, max.	1,50 mm ²
Torque level with DMS electric screwdriver	1

Dimensions

TS 35 offset	4 mm
TS 32 offset	5 mm
Width	6,1 mm
Length	41,5 mm
Height of lowest version	42,5 mm

Disconnect terminals

Torque level with DMS electric screwdriver	1
--	---

EN 60079-7 rating data

Voltage at cross-connection DU+QV skipping	175 V
Marking ATEX Directive 94/9/EC	II 2 G D
Marking ATEX Directive 94/9/EC	Ex II 2 G D
Marking EN 60079-7	Ex e II
Current Ex e	21 A
EC conformity verification certificate	KEMA 97ATEX1798 U
Voltage Ex e	550 V
Voltage at cross-connection DU+QV/DU+QV	550 V
Voltage Ex i, EN 50020	60 V
Voltage at cross-connection DU+QV/DU	550 V

Rating data

Rated cross-section	2,5 mm ²
Rated voltage	800 V
Rated impulse withstand voltage	8 kV
Rated current	24 A
Norm	IEC 60947-7-1
Current with max. conductor	41 A
Pollution severity	3

UL rating data

Voltage UL	600 V
Current (UL)	25 A
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

information boxes, print catalogue

Note, accessories	*UNDEFINED TEXT*
Note, technical data	To use twin ferrules is the rated voltage 630/690 V.

Approvals

Approvals



Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Related products

Order No.	Short text for material	Rated cross-section
0337660000	SAK 10/EN	10 mm ²

1784410000	SAK 10/EN BL	10 mm ²
0339760000	SAK 16/EN	16 mm ²
1784390000	SAK 16/EN BL	16 mm ²
0218680000	SAK 2.5/EN BL	2,5 mm ²
0339860000	SAK 35/EN	35 mm ²
1784400000	SAK 35/EN BL	35 mm ²
0467460000	SAK 4/EN	4 mm ²
0467480000	SAK 4/EN BL	4 mm ²
0212860000	SAK 6/EN	6 mm ²
0212880000	SAK 6/EN BL	6 mm ²