



General ordering data

Order No.	0467460000
Short text for material	SAK 4/EN
EAN	4008190002749
Qty	100

Additional technical data

No. of identical terminals	1
Type of connection	screwed
Type of mouting	clipped
Version	Feed-through terminal
Installation advice	TS 35 + TS 32
UL 94 flammability rating of insulation material	V2
Insulating material	Polyamide
Colour of insulating material	beige
Operating temperature range	- 50 °C, + 100 °C
Open sides	right
No. of levels	1
No. of terminal strips per level	2
Levels cross-connected internally	No
End plate required	Yes
Explosion-tested version "Ex e"	No
Connection direction	on side

CSA rating data

Voltage CSA	600 V
CSA current	36 A
Max. cross-section (CSA)	AWG 10
Min. cross-section (CSA)	AWG 26

Conductors for clamping (additional connection)

Min. conductor cross-section (UL)	AWG 12
Max. conductor cross-section (UL)	AWG 22
Min. conductor cross-section (CSA)	AWG 10
Max. conductor cross-section (CSA)	AWG 26

Conductors for clamping (rated connection)

Stripping length	12 mm
Type of connection	Screw connection
2nd type of connection	screwed
Solid, min.	0,5 mm ²
Twin wire-end ferrule, min.	0,50 mm ²
Twin wire-end ferrule, max.	2,50 mm ²
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A4
AWG conductor size, max.	5,26 mm ²
AWG conductor size, max.	AWG 10
Stranded, max.	4 mm ²
Stranded, min.	0,5 mm ²
AWG conductor size, min. (mm)	0,13 mm ²
AWG conductor size, min.	AWG 26
Connection direction	on side
Flexible, min.	0,5 mm ²
No. of connections	2
Tightening torque range	0.5...1.0 Nm
Solid, max.	6 mm ²
Flexible, max.	4 mm ²
Flexible with ferrule, max. (DIN 46228 pt 1)	4 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm ²
Flexible with ferrule, min. (DIN 46228 pt 1)	0,5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0,5 mm ²
Clamping range, max.	6 mm ²
Clamping range, min.	0,13 mm ²
Clamping screw	M 3
Torque level with DMS electric screwdriver	2

Dimensions

Width	6,5 mm
Weight	11,73 g
Length	42 mm
Height of lowest version	47,5 mm
TS 35 offset	0 mm
TS 32 offset	6 mm

Disconnect terminals

Torque level with DMS electric screwdriver	2
--	---

EN 60079-7 rating data

Voltage at cross-connection DU+QV/DU	550 V
Voltage at cross-connection DU+QV skipping	175 V
Marking ATEX Directive 94/9/EC	II 2 G D
Marking ATEX Directive 94/9/EC	Ex II 2 G D
Marking EN 60079-7	Ex e II
Current Ex e	28 A
EC conformity verification certificate	KEMA 97ATEX1798 U
Voltage Ex e	550 V
Voltage at cross-connection DU+QV/DU+QV	550 V
Voltage Ex i, EN 50020	60 V

Rating data

Rated cross-section	4 mm ²
Rated voltage	800 V
Rated impulse withstand voltage	8 kV
Rated current	32 A
Norm	IEC 60947-7-1
Current with max. conductor	41 A
Pollution severity	3


UL rating data

Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12
Voltage UL	600 V
Current (UL)	30 A

information boxes, print catalogue

Note, technical data	To use twin ferrules is the rated voltage 630/690 V.
----------------------	--

Approvals

Approvals	
-----------	---

Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Related products

Order No.	Short text for material
0337660000	SAK 10/EN
1784410000	SAK 10/EN BL

0339760000	SAK 16/EN
1784390000	SAK 16/EN BL
0218660000	SAK 2.5/EN
0218680000	SAK 2.5/EN BL
0339860000	SAK 35/EN
1784400000	SAK 35/EN BL
0467480000	SAK 4/EN BL
0212860000	SAK 6/EN
0212880000	SAK 6/EN BL