



#### General ordering data

Order No.	0212860000
Short text for material	SAK 6/EN
EAN	4008190065553
Qty	100

#### Additional technical data

No. of identical terminals	1
Type of connection	screwed
Type of mouting	clipped
Version	Feed-through terminal
Installation advice	TS 35 + TS 32
UL 94 flammability rating of insulation material	V2
Insulating material	PA 66
Colour of insulating material	beige
Operating temperature range	- 50 °C, + 100 °C
Open sides	right
No. of levels	1
No. of terminal strips per level	2
Levels cross-connected internally	No
End plate required	Yes
Explosion-tested version "Ex e"	No
Connection direction	on side

#### CSA rating data

Voltage CSA	600 V
CSA current	47 A
Max. cross-section (CSA)	AWG 6
Min. cross-section (CSA)	AWG 26

### Conductors for clamping (rated connection)

Stripping length	12 mm
Type of connection	Screw connection
Flexible, min.	0,5 mm <sup>2</sup>
2nd type of connection	screwed
Solid, min.	0,5 mm <sup>2</sup>
Twin wire-end ferrule, min.	0,50 mm <sup>2</sup>
Twin wire-end ferrule, max.	4,00 mm <sup>2</sup>
No. of connections	2
Tightening torque range	0.8... 1.6 Nm
Solid, max.	10 mm <sup>2</sup>
Flexible, max.	10 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	6 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	6 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228 pt 1)	0,5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0,5 mm <sup>2</sup>
Clamping range, max.	10 mm <sup>2</sup>
Clamping range, min.	0,33 mm <sup>2</sup>
Clamping screw	M 3.5
Torque level with DMS electric screwdriver	3
Blade size	4.0 x 0.8 mm
Gauge to IEC 60947-1	A5
AWG conductor size, max.	8,37 mm <sup>2</sup>
Stranded, max.	6 mm <sup>2</sup>
Stranded, min.	0,5 mm <sup>2</sup>
AWG conductor size, min.	AWG 22
Connection direction	on side

### Dimensions

Length	40 mm
Height of lowest version	47,5 mm
Width	8 mm

### Disconnect terminals

Torque level with DMS electric screwdriver	3
--	---

### EN 60079-7 rating data

Voltage at cross-connection DU+QV skipping	175 V
Marking ATEX Directive 94/9/EC	II 2 G D
Marking ATEX Directive 94/9/EC	Ex II 2 G D
Marking EN 60079-7	Ex e II
Current Ex e	36 A
EC conformity verification certificate	KEMA 97ATEX1798 U
Voltage Ex e	550 V
Voltage at cross-connection DU+QV/DU+QV	550 V
Voltage at cross-connection DU+QV/DU	550 V

### Rating data

Rated cross-section	6 mm <sup>2</sup>
Rated voltage	800 V
Rated impulse withstand voltage	8 kV
Rated current	41 A
Norm	IEC 60947-7-1
Current with max. conductor	57 A
Pollution severity	3

### UL rating data

Max. cross-section (UL)	AWG 8
Voltage UL	600 V
Current (UL)	40 A
Min. cross-section (UL)	AWG 22

### information boxes, print catalogue

Note, accessories	*UNDEFINED TEXT*
Note, technical data	To use twin ferrules is the rated voltage 630/690 V.

### Approvals

Approvals



### Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

### Related products

Order No.	Short text for material
0337660000	SAK 10/EN
1784410000	SAK 10/EN BL
0339760000	SAK 16/EN
1784390000	SAK 16/EN BL
0218660000	SAK 2.5/EN
0218680000	SAK 2.5/EN BL
0339860000	SAK 35/EN
1784400000	SAK 35/EN BL
0467460000	SAK 4/EN
0467480000	SAK 4/EN BL
0212880000	SAK 6/EN BL