




General ordering data

Order No.	1020180000
Short text for material	WDU 4 BL
EAN	4008190185237
Qty	100

Product notes

Note, ordering data	Rated voltage 400V when using cross-connection ZQV See section "W-series accessories" for colours available.
Note, technical data	Note max. current of terminal (41 A) when using WQV.



Additional technical data

Connection direction	on side
No. of identical terminals	1
Type of connection	screwed
Type of mouting	clipped
Version	Feed-through terminal
Installation advice	TS 35
UL 94 flammability rating of insulation material	V-0
Insulating material	Wemid
Colour of insulating material	blue
Operating temperature range	- 50 °C, + 120 °C
Open sides	right
No. of levels	1
Product range	W-Series
No. of terminal strips per level	2
Levels cross-connected internally	No
End plate required	Yes
Explosion-tested version "Ex e"	Yes

CSA rating data

Voltage CSA	600 V
CSA current	35 A
Max. cross-section (CSA)	AWG 10
Min. cross-section (CSA)	AWG 26

Conductors for clamping (1) with equal cross-section (rated connection)

Flexible with ferrule, max. (DIN 46228 pt 1)	1,5 mm ²
Solid, max.	2,5 mm ²
Flexible with ferrule, min. (DIN 46228 pt 1)	0,5 mm ²
Flexible, max.	1,5 mm ²
Solid, min.	0,5 mm ²
Flexible, min.	0,5 mm ²

Conductors for clamping (rated connection)

Connection direction	on side
Flexible, min.	0,5 mm ²
2nd type of connection	screwed
Solid, min.	0,5 mm ²
Twin wire-end ferrule, min.	0,50 mm ²
Zwillings-AEH, max.	2,50 mm ²
Stripping length	10 mm
Type of connection	Screw connection
No. of connections	2
Tightening torque range	0.5...1.0 Nm
Solid, max.	6 mm ²
Flexible, max.	6 mm ²
flexible w. ferrule AEH, max. DIN 46228-1	4 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm ²
flexible w. ferrule AEH, min. DIN 46228-1	0,5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0,5 mm ²
Clamping range, max.	6 mm ²
Clamping range, min.	0,13 mm ²
Clamping screw	M 3
Torque level with DMS electric screwdriver	2
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A4
AWG conductor size, max.	5,26 mm ²
AWG conductor size, max.	AWG 10
Stranded, max.	6 mm ²
Stranded, min.	1,5 mm ²
AWG conductor size, min.	0,13 mm ²
AWG conductor size, min.	AWG 26

Dimensions

Height of lowest version	47 mm
Width	6,1 mm
TS 35 offset	15 mm
Weight	10,40 g
Length	60 mm

Disconnect terminals

Torque level with DMS electric screwdriver	2
--	---

EN 60079-7 rating data

Voltage at cross-connection DU+QV/DU	750 V
Voltage at cross-connection DU+QV/PE	420 V
Marking EN 60079-7	Ex e II
Current Ex e	28 A
EC conformity verification certificate	KEMA 98ATEX1683 U
Voltage Ex e	690 V
Voltage Ex i, EN 50020	60 V
Voltage at cross-connection DU+QV skipping	110 V
Marking ATEX Directive 94/9/EC	II 2 G D
Marking ATEX Directive 94/9/EC	Ex II 2 G D
Voltage at cross-connection DU+QV/PE with end plate	750 V

Rating data

Rated cross-section	4 mm ²
Rated voltage	800 V
Rated impulse withstand voltage	8 kV
Rated current	32 A
Norm	IEC 60947-7-1
Current with max. conductor	41 A
Pollution severity	3

UL rating data

Max. cross-section (UL)	AWG 10
Min. cross-section (UL)	AWG 22
Voltage UL	600 V
Current (UL)	35 A

Approvals

Approvals



Downloads

STEP	1020180000_09253_WDU_4_BL_ST
------	------------------------------

Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Identical profiles from 2.5 to 10 mm² with uniform end and partition plates. An unsurpassed combination of many advantages!

Their small size compared to the respective rated cross-section makes the modular terminals with the compact design very popular.

Related products

Order No.	Short text for material
1020100000	WDU 4
1037810000	WDU 4 BR
1020120000	WDU 4 GE
1020160000	WDU 4 GN
1037800000	WDU 4 GR
1036760000	WDU 4 OR
1020140000	WDU 4 RT
1020110000	WDU 4 SW
1036700000	WDU 4 WS
1021000000	WDU 4/10
1020900000	WDU 4/10/BEZ