



#### General ordering data

Order No.	1010100000
Short text for material	WPE 4
EAN	4008190039820
Qty	100

#### Additional technical data

No. of identical terminals	1
Type of connection	screwed
Type of mouting	screwed
Version	PE terminal
Installation advice	TS 35
UL 94 flammability rating of insulation material	V-0
Insulating material	Wemid
Colour of insulating material	green/yellow
Operating temperature range	- 50 °C, + 120 °C
Open sides	closed
No. of levels	1
Product range	W-Series
No. of terminal strips per level	2
End plate required	No
Connection direction	on side

#### CSA rating data

Max. cross-section (CSA)	AWG 10
Min. cross-section (CSA)	AWG 26

**Conductors for clamping (rated connection)**

Stripping length	10 mm
Type of connection	Screw connection
No. of connections	2
Tightening torque range	0.5...1.0 Nm
AWG conductor size, max.	6,00 mm <sup>2</sup>
AWG conductor size, max.	AWG 10
Stranded, max.	6 mm <sup>2</sup>
Stranded, min.	0,5 mm <sup>2</sup>
AWG conductor size, min.	0,13 mm <sup>2</sup>
AWG conductor size, min.	AWG 26
Connection direction	on side
Flexible, min.	0,5 mm <sup>2</sup>
Solid, min.	0,5 mm <sup>2</sup>
Solid, max.	6 mm <sup>2</sup>
Flexible, max.	6 mm <sup>2</sup>
flexible w. ferrule AEH, max. DIN 46228-1	4 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm <sup>2</sup>
flexible w. ferrule AEH, min. DIN 46228-1	0,5 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0,5 mm <sup>2</sup>
Clamping range, max.	6 mm <sup>2</sup>
Clamping range, min.	0,13
Clamping screw	M 3
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A4
Torque level with DMS electric screwdriver	2

**Dimensions**

TS 35 offset	11 mm
Length	60 mm
Height of lowest version	47 mm
Width	6,1 mm

**Disconnect terminals**

Torque level with DMS electric screwdriver	2
--------------------------------------------	---

**EN 60079-7 rating data**

Marking EN 60079-7	Ex e II
EC conformity verification certificate	KEMA 98ATEX1683 U
Marking ATEX Directive 94/9/EC	II 2 G D
Marking ATEX Directive 94/9/EC	Ex II 2 G D

**PE rating data**

Torque level with DMS electric screwdriver	2
Tightening torque range for fixing screw	0.5...0.8 Nm
Rated short-time current	480 A (4 mm <sup>2</sup> )
Rated impulse withstand voltage to adjacent terminal	8 kV
PEN function	No
Norm	IEC 60947-7-2
Pollution severity	3
Rated cross-section	4 mm <sup>2</sup>
Centre screw on PE terminals	M 3
Rated voltage for adjacent terminal	800 V

**UL rating data**

Max. cross-section (UL)	AWG 10
Min. cross-section (UL)	AWG 22

**Approvals**

Approvals

**Downloads**

STEP	1010100000_24799_WPE_4_STP.s
------	------------------------------

**Classifications**

ETIM 2.0	EC000901
ETIM 3.0	EC000901
eClass 4.1	27-14-03-05
eClass 5.0	27-14-03-05
eClass 5.1	27-14-03-05

Identical profiles from 2.5 to 10 mm<sup>2</sup> with uniform end and partition plates. An unsurpassed combination of many advantages!

Their small size compared to the respective rated cross-section makes the modular terminals with the compact design very popular.

**Related products**

Order No.	Short text for material
1036300000	WDK 2.5PE
1752520000	WDK 2.5PE/E
1016500000	WPE 1.5/ZZ
1010300000	WPE 10
1042500000	WPE 10/ZR
1019700000	WPE 120/150
1010400000	WPE 16
1010000000	WPE 2.5
1016400000	WPE 2.5/1.5/ZR

1010500000	WPE 35
1010200000	WPE 6
1037300000	WPE 70/95