

**A-series  
ZQV 4N/2**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | ZQV 4N/2                   |
| Order No.  | <a href="#">1527930000</a> |
| GTIN (EAN) | 4050118332766              |
| Qty.       | 60 pc(s).                  |

**A-series  
ZQV 4N/2**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

|            |          |                 |           |
|------------|----------|-----------------|-----------|
| Width      | 9.9 mm   | Width (inches)  | 0.39 inch |
| Height     | 2.8 mm   | Height (inches) | 0.11 inch |
| Depth      | 27.95 mm | Depth (inches)  | 1.1 inch  |
| Net weight | 1.371 g  |                 |           |

**Temperatures**

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -60 °C | Continuous operating temp., max. | 130 °C |
|----------------------------------|--------|----------------------------------|--------|

**Material data**

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | Wemid | Colour | Orange |
| UL 94 flammability rating | V-0   |        |        |

**Additional technical data**

|                          |     |                |         |
|--------------------------|-----|----------------|---------|
| Explosion-tested version | Yes | Type of fixing | Plugged |
|--------------------------|-----|----------------|---------|

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

**Rating data**

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 6.0   | EC000489    | eClass 6.2 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 |            |             |

**Approvals**

Approvals



ROHS Conform

**Downloads**

|   |  |
|---|--|
| Approval/Certificate/Document of Conformity | <a href="#">IECEXULD14.0005U_e.pdf</a>             |
| Brochure/Catalogue                          | <a href="#">CAT 1 TERM 16/17 EN</a>                |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>           |
| Engineering Data                            | <a href="#">STEP</a>                               |
| User Documentation                          | <a href="#">2434520000_BED-ANL.ZQV_A_REIHE.pdf</a> |