

Completely pre-assembled Signal Towers / KOMPAKT 37
K37 plug EM 24VAC/DC GN/RD



Part No.:	698.220.75
Series:	Kompakt 37



MECHANICAL DATA

Height	141 mm
Diameter	38 mm
Materials	PC
Cap colour	Green Red
Housing colour	Black
Protection category	IP65
Connection	M12 plug 5-pole
Cable entry	Membrane grommet
Cable entry minimum	d = 1 mm
Cable entry maximum	d = 9 mm
Tension relief	Pull-out protection
Type of fixing	Built-in mounting
Service life optical	50,000 h maximum
Working temperature minimum	-20°C
Working temperature maximum	+50°C
Weight with packaging in g	112 g
Product weight in g	73 g

ELECTRICAL DATA

Voltage	24V
voltage type	AC/DC
Total current consumption	70 mA
Starting current	500 mA


OPTICAL DATA

Light source	LED
Light colour	Green Red
Optical signal image	Duration

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Completely pre-assembled Signal Towers / KOMPAKT 37
K37 plug EM 24VAC/DC GN/RD

DRAWING



! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.