



Base mounting



Plastic bracket und wire guard (accessories)

- High light intensity in compact form
- Award-winning design – winner of the “iF product design award 2006”
- Extremely quiet
- Can be mounted as required
- Installation without the need to disassemble the mechanism

TECHNICAL SPECIFICATIONS:

Dimensions (Ø x Height):	98 mm x 151 mm
Housing:	PC/ABS-Blend
Lens:	PC, transparent
Fixing:	Base mounting, bracket mounting (accessory)
Connection:	Screw terminal with wire protection max. 2.5 mm ² Contact protection according to VDE
Cable entry:	Cable diameter 5-7 mm
Installation position:	As required
Halogen bulb:	G 6.35 20 W 12 V / 24 V
Mirror rotation rate:	c. 180 r.p.m.
Service life of drive:	> 5,000 hrs
Duty cycle:	100 %

Halogen bulb included in assembly.

ORDER SPECIFICATIONS:

Voltage	12 V =	24 V ≈	115 V ~ / 115 V =	230 V ~ / 230 V =
Current consumpt.	1.7 A	1.0 A	0.35 A / 0.2 A	0.15 A / 0.1 A
red	885 100 54	885 100 75	885 100 78	
green	885 200 54	885 200 75	885 200 78	
yellow	885 300 54	885 300 75	885 300 78	
blue	885 500 54	885 500 75	885 500 78	

ACCESSORIES:

Halogen bulb for wall mounting	975 826 05
Wire guard, galvanised, only for base mounting	975 826 03

SPARE PARTS:

Halogen bulb 20 W/12 V for 12 V = 115 V ≈, 230 V ~	955 885 24
Halogen bulb 20 W/24 V for 24 V ≈	955 885 25

TECHNICAL DIAGRAMS:

see page 290

Sizes of Rotating Beacons

